

Description AGRI-FLEX™ 10 is a natural low dust granular high purity Wyoming sodium bentonite. It is used as a binder and rheological modifier. It has application that aids in pellet binding in fowl and animal feed pellet production. It will insure tougher more durable pellets. It aids in the free movement of pellets to prevent lumping and caking.

Applications/Functions

- Aids in pellet binding for animal feed pellet production

Advantages

- Insures tougher more durable pellets
- Increased flowability of pellets
- Aids in prevention of lumping and caking

Screen Analysis	Typical	Specification
• Dry screen, percent plus 10 mesh	•	• 30 Max
• Dry screen, percent minus 70 mesh	•	• 1.0 Max
• Dry screen, percent minus 200 mesh	•	• 0.5 Max

Properties	Typical	Specification
• Moisture, percent	•	• 12 Max
• Specific Gravity	• 2.7	•
• Bulk Density (lbs/ft ³ compacted)	• 73	•
• Bulk Density (lbs/ft ³ uncompacted)	• 65	•

Availability AGRI-FLEX™ 10 can be purchased through any Bentonite Performance Minerals LLC assigned Reseller. To locate the BPM Reseller nearest you, contact the Customer Service Department in Houston or your area BPM Regional Sales Manager.

Bentonite Performance Minerals LLC
A Halliburton Company
 3000 N. Sam Houston Pkwy E.
 Houston, TX 77032
www.bentonite.com

Customer Service (281) 871-7900 **Fax** (281) 871-7940