

**Description** AGRI-FLEX™ 8 is a natural low dust granular high purity Wyoming sodium bentonite. It is used as a binder and rheological modifier. It has application that aids in pellet binding in fowl and animal feed pellet production. It will insure tougher more durable pellets. It aids in the free movement of pellets to prevent lumping and caking.

**Applications/Functions**

- Aids in pellet binding for animal feed pellet production.

**Advantages**

- Insures tougher more durable pellets.
- Increased flowability of pellets.
- Aids in prevention of lumping and caking.

<b>Screen Analysis</b>	<u>Typical</u>	<u>Specification</u>
• Dry screen, percent plus 8 mesh	•	• 15 Max
• Dry screen, percent minus 20 mesh	•	• 20 Max
• Dry screen, percent minus 200 mesh	•	• 5 Max

<b>Properties</b>	<u>Typical</u>	<u>Specification</u>
• Moisture, percent	•	• 12 Max
• Specific Gravity	• 2.7	•
• Bulk Density (lbs/ft <sup>3</sup> compacted)	• 71	•
• Bulk Density (lbs/ft <sup>3</sup> uncompactd)	• 65	•

**Availability** AGRI-FLEX™ 8 can be purchased through any Bentonite Performance Minerals LLC assigned Reseller. To locate the BPM Reseller nearest you, contact the Customer Service Department in Houston or your area BPM Regional Sales Manager.

**Bentonite Performance Minerals LLC**  
**A Halliburton Company**  
 3000 N. Sam Houston Pkwy E.  
 Houston, TX 77032  
[www.bentonite.com](http://www.bentonite.com)

**Customer Service** (281) 871-7900      **Fax** (281) 871-7940