

Description NATIONAL[®] PREMIUM WT is a natural 200 mesh Wyoming sodium bentonite. It is used as a binder, stabilizer, suspension agent, and rheological modifier. It has application as an additive for foundry coatings, industrial coatings, detergents, paper, ceramics and household products.

Applications/Functions

- Binder, stabilizer and suspension agent to impart rheological properties to aqueous systems
- Foundry coatings, industrial coatings
- Detergents, paper, ceramics and household products

Advantages

- Imparts low viscosity
- Superior stability in the presence of organic compounds

Screen Analysis

	<u>Typical</u>	<u>Specification</u>
• Dry screen, percent minus 200 mesh	•	• 67.5 Min

Properties

	<u>Typical</u>	<u>Specification</u>
• Moisture, percent	•	• 12 Max
• Specific Gravity	• 2.7	•
• Bulk Density (lbs/ft ³ compacted)	• 73	•
• Bulk Density (lbs/ft ³ uncompacted)	• 53	•

Availability NATIONAL[®] PREMIUM WT can be purchased through any Bentonite Performance Minerals LLC assigned Reseller. To locate the BPM Reseller nearest you, contact the Customer Service Department in Houston or your area BPM Regional Sales Manager.

Bentonite Performance Minerals LLC
A Halliburton Company
3000 N. Sam Houston Pkwy E.
Houston, TX 77032
www.bentonite.com

Customer Service (281) 871-7900 **Fax** (281) 871-7940