



NATIONAL[®]

STANDARD SPCL GRIND Bentonite

Description NATIONAL[®] STANDARD SPCL GRIND is a high yield, special mesh grind, Wyoming sodium bentonite. It is used as a binder, stabilizer, suspension agent, and rheological modifier. It has application as an additive for industrial coatings and ceramics.

Applications/Functions

- Manufacturing of mixed mineral ceramics

Advantages

- Binder
- Stabilizer
- Rheological modifier

Screen Analysis	<u>Typical</u>	<u>Specification</u>
• Dry screen, percent minus 200 mesh	•	• 90 Min
• Wet screen, percent minus 200 mesh	•	• 97 Min
• Wet screen, percent minus 325 mesh	•	• 95 Min

Properties	<u>Typical</u>	<u>Specification</u>
• Moisture, percent	•	• 12 Max
• Specific Gravity	• 2.7	•
• Bulk Density (lbs/ft ³ compacted)	• 70	•
• Bulk Density (lbs/ft ³ uncompacted)	• 48	•

Availability NATIONAL[®] STANDARD SPCL GRIND can be purchased through any Bentonite Performance Minerals LLC assigned Reseller. To locate the BPM Reseller nearest you, contact the Customer Service Department in Houston or your area BPM Regional Sales Manager.

Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E.

Houston, TX 77032

www.bentonite.com

Customer Service (281) 871-7900 **Fax** (281) 871-7940